



Hand pallet truck – stainless steel

Built to withstand hard and continuous usage in the food industry. Pump cylinder, tilting arms and ram bars made of hot galvanized special steel. Available with single or tandem fork wheels. Nylon or polyurethane (PU) wheels and fork wheels, lifting height of 90-200 mm, length of forks 1,130 mm, width of forks 520 mm (standard).

Equipment:

- Custom-made on request
- Climbing rolls for easy insertion into the pallets
- Free loading of fork
- Matt surface

- A) Nylon single wheel white
- B) Nylon tandem wheel white
- C) Nylon single wheel redbrown
- D) Nylon tandem wheel redbrown



VA-Gabelhubwagen

Robuste Ausführung speziell für den Einsatz in der Fleisch- und Lebensmittelindustrie gefertigt. Pumpe, Querträger und Einzelteile im Unterwagen aus Spezialstahl verzinkt. Lieferbar mit Nylon- oder Polyurethanrollen (PU). Tandem- oder Einzelgabelrollen. Hubhöhe 90 – 200 mm, Gabelabmessungen Standard 1.130 x 520 mm.

Ausstattung:

- Sondermaße auf Anfrage
- Kletterrollen für leichtes Quereinfahren in Paletten
- Lastfreistellung der Gabel
- Mattierte Oberfläche

- A) mit Nylon-Einzelrollen weiß
- B) mit Nylon-Tandemrollen weiß
- C) mit PU-Einzelrollen rotbraun
- D) mit PU-Tandemrollen rotbraun

			Art.-Nr.
A	2.500 kg	~ 75 kg	5007 2510
B	2.500 kg	~ 75 kg	5007 2520
C	2.500 kg	~ 75 kg	5007 2530
D	2.500 kg	~ 75 kg	5007 2540