



High Pressure Cleaningmachine HDW N2 for Birail-Hooks with intensive dirt

Up to 1,200 pieces/h



- Operation by Touch Panel
- Weekly timer
- Extensive user information





Functional principle

At the entrance of the machine the polluted meathooks will be picked up by the conveyor which transports the hooks through the machine.

A special developed and patented jetsystem device, which can be adjusted individually, will be supplied by a high pressure pump.

The specific cleaning effect will be achieved by function of oszillating jets. So, the jet of water will reach every point of the hooks surface.

In the exit area of the machine, the installed shower enables to remove any debris of detergent or dirt. Likewise, the operating with hot water desinfects the hooks.

A precise and economical dosing of detergent contributes to the cleaning results as well as a constant temperature regulation of the raw water.

Advantages, you can profit of!

- Very good cleaning results. This applies to hooks with an intensive dirt also.
- Even labels, bristles or pieces of meat will be eliminated in coordination with special cleaning agent.
- 3. High capacity
- 4. Good cost effectiveness
- 5. Compact construction
- 6. Fullautomatically function by the option of programming a weekly timer or method of cleaning
- 7. Selfcleaning abilities
- 8. Less maintenance costs
- 9. Environmentally fiendly
- Cost savings in obtaining and removing the waste (detergent and effluences)
- 11. Easy implementation into already existing convey systems
- Can be used as a stand alone system without any further systems. Manual loading.
- 13. Short installation time
- 14. User-friendly



Equipment

- Fullautomatically control system through PLC SIEMENS S7 1200
- Operation by comfortable touchpanel and optimal menu navigation (SIEMENS TP700)
- The speed of the conveyor is variable adjustable. A precise adjustment to the required hooks is possible.
- High value pumps. All water contacted parts are made of stainless steel
- Possibility to dose the detergent individual
- Continuous regulation of temperature
- Efficient temperature performance
- Quick and easy maintenance due to openings at its sides
- The hook shower at the exit of the machine can be adjusted as required. Included with InlineJet the hookshowering on the glidingpoint of hooks. New and exclusively at Marchel
- Shower can be used with hot or cold water

Non-Polluting

Marchel cleaning devices combines ecological and economical performance, because the raw water will be recycled in a closed ciruit. This enables to optimise the fresh water consumption, the energy usage, the detergent as well as the effluent.


Options by equipment:

- Extra jet for cleaning running gear
- Extra jet for cleaning transponder
- Extra protection door for panel




Filtering and control unit with capacity of 550 liters









View of heating control

| Technical Data | Cleaning capacity 600 Hooks/h | Cleaning capacity 1.200 Hooks/h |
|---------------------------|--------------------------------------|--------------------------------------|
| | ArtNo. 5300 1121 | ArtNo. 5300 1122 |
| Voltage | 400 V/50-60 Hz | 400 V/50-60 Hz |
| Rated power supply | 60 kVA | 100 kVA |
| Heating | 44 kW | 88 kW |
| Mainpump | 4,0 kW | 4,0 kW |
| Dimensions cleaning unit | L 4.000 (2.900) x B 900 x H 1.450 mm | L 4.000 (2.900) x B 900 x H 1.450 mm |
| Dimensions filtering unit | L 1.900 x B 1.000 x H 2.100 mm | L 3.400 x B 1.000 x H 2.100 mm |
| Process water in use | 550 Liter | 1.100 Liter |
| Open passage | W 360 mm x H 590 mm | W 360 mm x H 590 mm |

Marchel empty hook transport system

Empty hook transport systems are a rational supplement to the high pressure cleaning machines.

Outstanding engineering, know-how and services will convince you of our products.

Please contact us for an individual offer.

Heinz Marchel GmbH & Co. KG

Ringstraße 3 49134 Wallenhorst GERMANY

Phone: +49 (0) 5407/8989-0 Fax: +49 (0) 5407/8989-79

www.marchel.de

E-Mail: info@marchel.de